

Shell Kit for Ecolift, w/o socket, tileable

Article information

Item no.: 21000X-RBK
GTIN: 4026092097120
Price group: 20

Description

KESSEL shell kit for Ecolift, without sockets, tileable

Shell kit consisting of a drain body, upper section and flange for joint sealing. The inlet and outlet sockets are not included.

For combination with a KESSEL technology kit for creating an Ecolift backwater lifting station.

General characteristics

| | |
|----------------------------|--|
| Colour: | black |
| Type of wastewater: | with sewage |
| Installation situation: | floor slab installation |
| Delivery state: | Pre-mounted for final assembly on site (pumps and sensor system must be fitted on site and control unit must be connected) |
| Approval: | Z-53.2-487 |
| Motor type: | KSM 140 |
| Type de protection moteur: | IP 68 (3m/48h) |
| ATEX: | no |

Dimensions

| | |
|--|-------------------------------------|
| Net weight: | 25 kg |
| Gross weight: | 30,5 kg |
| Groundwater resistant from lower edge of base section: | 3000 mm |
| Installation depth: | 516 - 669 mm |
| Type of height adjustability: | vertically adjustable upper section |
| Length: | 590 mm |
| Width: | 590 mm |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |

Tank/drain body

| | |
|--------------------------------|----------|
| Nominal pressure (PN): | 6 |
| Pressure pipe connection (OD): | 40 mm |
| Socket version: | optional |

Coverage features

| | |
|-----------------------|----------------------|
| Type of cover: | tileable cover plate |
| Cover material: | Polymer |
| Width of cover: | 366 mm |
| Length of cover: | 366 mm |
| Drainage function: | yes |
| Locking: | Lock & Lift |
| Load class: | K 3 (EN 1253-1) |
| Max. flooring height: | 16 mm |
| Odour trap: | Multistop |