


Practicus drain body Press. fl., DN 50, Vertical outlet



Article information

Item no.: 45259
 GTIN: 4026092033807
 Price group: 10

Advantages

- Hygiene: hygienic, absolutely corrosion-free and durable material
- absolutely corrosion-free and durable material
- Fire protection: combinable with the Fire-Kit for fire and smoke protection

Description

In combination with an upper section, the Practicus polymer drain body is used for point drainage and is equipped with a removable odour trap and a temporary protective cover. The drain meets particular sound insulation requirements in accordance with the measurements of the Fraunhofer Institute in Stuttgart.

Variant

System:	125
Waterproofing layer on the upper section:	Enclosed sealing collar to be glued (bd) according to DIN 18534
Waterproofing layer on the drain body:	Press sealing flange (suitable for creating watertight seals)
Sealing water height:	50 mm
General characteristics	
Nominal size (DN):	50
Outer diameter (OD):	50 mm
Approval:	Z-19.53-2414,Z-19.17-1719
ATEX:	no
Odour trap:	included

Dimensions

Net weight:	1,77 kg
Gross weight:	2,06 kg

Diameter:	273 mm
Height:	207 mm
Packaging dimension:	length
Packaging dimension:	width
Packaging dimension:	height
Tank/drain body	
Number of outlets:	1
Material of drain body:	PP
Socket version:	vertical