



Variofix upper section Designrost Spot, V2A, Lock & Lift, K 3





Article information

Item no.: 48621 GTIN: 4026092044827 Price group: 10

Advantages

- Different covers selectable
- Including waterproofing membrane

Description

Used in combination with a drain body of the KESSEL modular system, the upper section is suitable for indoor point drainage.

| Variant System: Waterproofing layer on the upper section: Water exposure class in accordance to DIN 18534-1 (up to and including): | 125 Enclosed sealing collar to be glued (bd) according to DIN 18534 W3-I |
|--|---|
| General characteristics | |
| ATEX: | no |
| Dimensions | |
| Vertical adjustment: | 10 - 23 mm |
| Net weight: | 1,5 kg |
| Gross weight: | 1,74 kg |
| Diameter: | 312 mm |
| Type of height adjustability: | vertically adjustable upper section |
| Height: | 120 mm |
| Packaging dimension: | length |
| Packaging dimension: | width |
| Packaging dimension: | height |
| | |

Coverage features



Type of cover: Cover material: Colour of cover: Locking: Load class: Grating design: Rim width: Rim length: Upper section: Shape of upper section: Upper section material: Design cover Stainless steel 14301 silver Lock & Lift K 3 (EN 1253-1) Spot 132 mm 132 mm adjustable in three dimensions square ABS