

Parking deck drain, Ecoguss Pressure sealing flange, DN 100, square



Article information

Item no.: 48811.01 GTIN: 4026092036099 Price group: 40

Advantages

- Breakproof & load resistant
- withstand temperatures up to 400 degrees Celsius

Description

Variant

The Ecoguss parking deck drain is used for point drainage and is equipped with a sludge bucket. The recyclable composite material Ecoguss is temperature resistant and has a permanently corrosion-free surface. The outlet socket is suitable for connection to SML cast iron pipes. Separate equipotential bonding is not necessary. For products with pressure sealing flange: The pressure sealing flange with bolts and screws made of stainless steel is used for the clamping or welding of bitumen and polymer bitumen sheets as well as for polymer and elastomer sealing sheets. Only membranes tested by the manufacturer may be used for watertight seals. The outlet socket is suitable for connection to SML cast iron pipes. With connection option for equipotential bonding. It can be exposed to flames for short periods, 100 up to 400 degrees Celsius.

125 yes Press sealing flange (suitable for creating watertight seals) 4,5
EN 1253-2
100
110 mm
no
4,88 kg
5,87 kg
290 mm
300 mm
300 mm
290 mm



Width: Packaging dimension: Packaging dimension: Packaging dimension:

Tank/drain body Material of drain body: Socket version:

Coverage features Type of cover: Cover material: Colour of cover: Width of cover: Length of cover: Surface: Frame material: Locking: Load class: Rim width: Rim length: Shape of upper section: Upper section material: Contents of sludge trap: 290 mm length width height

Ecoguss vertical

Round slotted cover Ecoguss black 234 mm 234 mm EDM Ecoguss Lock & Lift B 125 (EN 124) 247 mm 247 mm square Ecoguss yes