


Upper section with slotted cover d: 218 mm, A/L15



Article information

Item no.: 67986
 GTIN: 4026092085493
 Price group: 10

Advantages

- Multiple combinations with suitable drain bodies

Description

The polymer upper section is suitable for LW 400 chamber systems and is equipped with a clamping ring and a hanger for sludge buckets. Continuously height-adjustable by 440 mm. If installed in roads, parking areas and comparable hard-surfaced traffic areas for trucks (Class D), the upper section must be underlaid on site with an approx. 15 cm thick reinforced supporting slab with at least 0.80 x 0.80 m made of B35 concrete. The exact design of the concrete slab must be calculated structurally according to the circumstances on site. A standard formwork and reinforcement drawing can be provided.

Variant

System: 200

General characteristics

ATEX: no

Dimensions

Net weight: 4,4 kg
 Gross weight: 4,9 kg
 Diameter: 218 mm
 Type of height adjustability: vertically adjustable upper section
 Packaging dimension: length
 Packaging dimension: width
 Packaging dimension: height

Coverage features

Cover material:	Polymer
Colour of cover:	black
Load class:	A 15 (EN 124) / L 15 (EN 1253-1)
Rim width:	300 mm
Rim length:	300 mm
Upper section material:	Polymer