


Replacement pump pumping station dry installation SPF 4500-S1



Article information

Item no.: 680534
GTIN: 4026092074954
Price group: 90

Description

Replacement pump type SPF 4500-S1 for Aqualift FXL pumping station, dry installation

Variant

Pump control: Control unit

General characteristics

Cable length: 10 m
ATEX: no

Dimensions

Net weight: 33,2 kg
Gross weight: 36 kg
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Pumping device

Pump: SPF 4500
Connection type: Direct connection
Operating voltage: 400 V
Mains frequency: 50 Hz
Rated current: 7,5 A
Protection class: I
Insulation class: F
Cos phi - power factor: 0,85
Protection class (pump): IP 68
Max. temperature (permanent) of conveyed material: 40 °C
Max. pumping height: 20 m
Speed: 2850 U/min
Power P1: 4,2 kW
Power P2: 3,5 kW

Operating mode:	S3 - 50 %
Type of fuse required (electrical protection):	Fuse protection through control unit 400 V
Type of pump connection cable:	H07RN-F 7G 1.5 mm ²
Length of mains cable for pump:	10 m
Control	
Connection type:	Direct connection
Type of fuse required (electrical protection):	Fuse protection through control unit 400 V