

Replacement pump GTF 1250 w. float switch, Aqualift S 100/200, 5m



Article information

Item no.: 680978
 GTIN: 4026092095911
 Price group: 90

Description

Replacement pump with float switch for faecal-free wastewater.

Variant

Pump control: Float switch

General characteristics

Type of wastewater: without sewage

Dimensions

Net weight: 10,5 kg
 Gross weight: 10,5 kg
 Packaging dimension: length
 Packaging dimension: width
 Packaging dimension: height

Pumping device

Pump: GTF 1250
 Connection type: Schuko (earthed contact) 2-pin
 Rated current: 5,4 A
 Length of mains cable for pump: 5 m
 Protection class (pump): IP 68 (3m)
 Max. temperature (permanent) of conveyed material: 40 °C
 Max. pumping height: 11 m
 Speed: 2700 U/min
 Power P1: 1,3 kW
 Power P2: 0,8 kW
 Operating mode: S3 - 50 %
 Type of fuse required (electrical protection): C 16 A
 Type of pump connection cable: H07RN-F 3G 1.5 mm²
 Impeller type: Multi-vane impeller

Control

Mains frequency:

50 Hz

Operating voltage:

230 V

Connection type:

Schuko (earthed contact) 2-pin

Rated current:

5,4 A