

Backwater valve Staufix DN 200, exposed, Type 2 R



Article information

Item no.: 730200R GTIN: 4026092076187 Price group: 10

Advantages

- Optional rat protection flap for additional safety
- Flexible installation, various covers available for floor slab installation
- Alternatively available as a module set

Description

The backwater valve for wastewater without sewage is equipped with two mechanical flaps which close automatically in the event of backwater. One flap serves as an emergency closure to be closed by hand. Thanks to the modular KESSEL system, existing systems can easily be converted to the StaufixControl backwater valve.

Variant Stainless steel flap as rat protection: Emergency closure: Mechanical backwater flaps:	yes yes 2
General characteristics Colour: Standard: Nominal size (DN): Outer diameter (OD): Note on nominal size: Type of wastewater: Installation situation: Delivery state: Backwater protection:	black EN 13564 200 200 mm Hydraulics correspond to DN 150 without sewage exposed drainage pipe installation-ready Type 2
Dimensions Net weight: Gross weight: Vertical drop between inlet and outlet: Length: Width: Height: Packaging dimension:	3,8 kg 6,4 kg 8 mm 586 mm 233 mm 306 mm length



Packaging dimension: Packaging dimension:

Coverage features Type of cover: Cover locking: width height

Lockable cover One-handed closure