

Sampling chamber LW 400, DN 100/150, class D



Article information

Item no.: 915880D
 GTIN: 4026092025062
 Price group: 60

Description

Sampling chamber LW 400 for separators, for underground installation, draining, watertight, resistant to aggressive wastewater. Minimum installation depth can be achieved by sawing to required length. Flow direction:

straight A load distribution slab must be installed on site for load class D. The reinforcement drawings are available from KESSEL.

General characteristics

Colour: black
 Material: PE

Dimensions

Net weight: 39 kg
 Gross weight: 45 kg
 Vertical drop between inlet and outlet: 120 mm
 Installation depth: 400 - 1300 mm
 Vertical adjustment: vertically adjustable upper section
 Packaging dimension: length
 Packaging dimension: width
 Packaging dimension: height

Tank/drain body

Distance pipe bottom inlet to tank bottom: 120 mm
 Outlet nominal size (OD): 110 mm
 Outlet nominal size (DN): 100 mm
 Inlet nominal size (OD): 110 mm
 Inlet nominal size (DN): 100 mm
 Clear width of tank (LW): 400 mm

Coverage features

Type of cover: Cover plate
 Cover material: Grey iron
 Colour of cover: black
 Load class: D 400 (EN 124)

Tightness:

odour-tight and surface water resistant