

Sampling chamber d: 450 mm, DN 100, Class D



Article information

Item no.: 915881D GTIN: 4026092055410

Price group: 60

Description

Sampling chamber LW 450 for separators, for underground installation, draining, watertight, resistant to aggressive wastewater. Minimum installation depth can be achieved by sawing to required length. Flow direction:

straight A load distribution slab must be installed on site for load class D. The reinforcement drawings are available from KESSEL.

General characteristics

Colour: black Material: PE ATEX: no

Dimensions

Net weight: 47 kg
Gross weight: 53 kg
Vertical drop between inlet and outlet: 160 mm
Installation depth: 950 - 1300 mm

Type of height adjustability: vertically adjustable upper section

Length: 730 mm
Packaging dimension: length
Packaging dimension: width
Packaging dimension: height

Tank/drain body

Distance pipe bottom inlet to tank bottom:

Outlet nominal size (OD):

110 mm

Outlet nominal size (DN):

100 mm

Inlet nominal size (DN):

110 mm

Clear width of tank (LW):

205 mm

110 mm

100 mm

450 mm

Coverage features

Type of cover: Cover plate Cover material: Grey iron



Colour of cover: Load class:

Tightness:

black

D 400 (EN 124)

odour-tight and surface water resistant