

## EasyClean round grease separator free, NS 15, Mix

### Article information

Item no.: 93015.05/DS  
GTIN:  
Price group: 60

### Advantages

- Simple control
- Low-maintenance operation
- Odour-reduced disposal with the tank closed

### Description

The separator for greasy wastewater is suitable for free-standing set-up in frost-protected rooms and is manufactured without the need for metallic internal structural components. The collection tank made of permanently resistant polymer (PE) is equipped with an integrated sludge trap and has sloped sides in the base to promote fast and efficient disposal. Two odour-tight covers with quick-release closures make easy access possible for cleaning and maintenance work. The innovative Shredder-Mix System with integrated macerating system homogenises and circulates the tank contents. Cleaning is carried out via an exterior pump which can be disconnected from the tank by a shut-off valve. A direct disposal pipe socket is available for odour-neutral manual disposal. 20 year polyethylene warranty.

#### Variant

Shut-off valve:	yes
Disposal variant:	Mix
Shredder-Mix-System:	yes
Sludge bucket:	no
Nominal size (NS):	15
SonicControl:	no
Type of disposal:	manual
Load-bearing capacity (DIN 19901):	F3

#### General characteristics

Material:	PE
Standard:	EN 1825
Installation situation:	free-standing installation

#### Dimensions

Net weight:	710 kg
Gross weight:	710 kg
Set-up area, length:	2230 mm
Set-up area, width:	1922 mm
Set-up area, height:	2020 mm
Required access area, length:	2230 mm
Required access area, width:	1880 mm
Required access area, height:	2020 mm

#### Tank/drain body

Nominal pressure (PN):	10
------------------------	----

Pressure pipe connection (DN):	65
Pressure pipe connection (OD):	75 mm
Distance pipe bottom outlet to tank bottom:	1550 mm
Distance pipe bottom inlet to tank bottom:	1620 mm
Outlet nominal size (OD):	200 mm
Outlet nominal size (DN):	200 mm
Inlet nominal size (OD):	200 mm
Inlet nominal size (DN):	200 mm
Connection inlet/outlet sockets:	PE-HD pipes in accordance with DIN 19537, HT pipes in accordance with DIN 19560, PP or AS

#### Coverage features

Type of cover:	Cover
Cover material:	Polymer
Colour of cover:	black
Locking:	Quick-release closure
Tightness:	odour-tight

#### Wastewater contents

Separator contents:	2300 l
Contents of sludge trap:	1500 l

#### Control

Control unit:	no
---------------	----